

**DECLARATION OF PERFORMANCE (acc. EU 305/2011, Annex III)
No 06-0001-04**

- 1. Unique identification code of the product-type:** STEICOmultip UDB
- 2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4) of the CPR :** see product label
- 3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:** Highly vapour-permeable airtight membrane
- 4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):** STEICO SE, Otto-Lilienthal-Ring 30, D-85622 Feldkirchen, email: info@steico.com
- 5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):** not relevant
- 6. System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V:** AVCP 3
- 7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:**
CENTRUM STAVEBNIHO INZENYRSTVI a.s., Pražská 16, CZ-Hostivar 10221 Praha 10, notified certification body No. 1390

8. Declared performance

Table 1


Essential characteristics	Desired value	Tolerance		Harmonised technical specification
		min.	max.	
Length [m]	50			EN 13859-1:2010
Width [m]	1,5	-0,5%	+1,5%	
Fire behaviour	E			
Resistance to water penetration	W 1			
Resistance to water penetration after ageing	W 1			
Area weight [g/m ²]	165	-10	+15	
Resistance to air penetration [m]	0,02	-0,01	+0,02	
Tensile force longitudinal/transverse [N/50mm]	290 / 210	-30/-30	+50/+50	
Tensile force after ageing longitudinal/transverse [N/50mm]	240 / 175	-15/-30	+70/+70	
Elongation tensile force longitudinal/transverse [%]	50 / 90	-15/-30	+25/+40	
Elongation after ageing longitudinal/transverse [%]	35 / 65	-15/-30	+30/+45	

Table 1 (continued)

Essential characteristics	Desired value	Tolerance		Harmonised technical specification
		min.	max.	
Tear resistance longitudinal/transverse [N]	220 / 280	-40/-60	+50/+70	EN 13859-1:2010
Cold bending [°C]	-20			
Dimensional stability [%]	<2			
Temperature resistance	-40 to +80			
Water pressure resistance	> 400			
Resistance to driving rain	yes			
Outdoor exposure	3			
Classification ZvDH	UDB-A + USB-A			

9. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8.

Signed for and on behalf of the manufacturer by:

Dr. Michael Makas Head of R&D/QM (name and function)	Feldkirchen, 22/01/2015 (place and date of issue)	b.o. (signature) 
--	--	--

Date: 21/06/2013	Revised: 22/01/2015
------------------	---------------------